


Product Group GGH 2000

Heavy duty (intended use) articulated glides with soft, non-slipping and silencing plastic slide base (from Ø 30 mm qualified for sport floors DIN 18032)




Standard Colours

- black RAL 9005

Material

- Base body: Polyamide (PA 6)
- Slide base: elastic partly vulcanised thermoplast (TPE-V)



Product information

- Suitable for wet rooms and outdoor seating
- The abrasion of the sliding surface depends on the condition of the floor (surface, soiling of the floor, etc.) and the load on the chair (must be tested by the user, the manufacturer cannot provide any guarantee).
- The article groups GGx2000 have been tested by the LGA with a displacement test and a tilt/fall test and are randomly tested annually. The tilt and fall test is already a test procedure that goes far beyond the normal or intended use of the chairs. In the event that chairs are pushed with momentum against fixed floor thresholds, we cannot accept any warranty, although moving chairs against floor thresholds is not critical for the intended use by the user. When stacking chairs and for contract seating, ensure that the floor is level and free of cracks and solid floor thresholds.
- e.S. = extra shank
- Series GGx2000 are patented.
- Patent 23 312 EP/PCT - DE 199 23 320
- The shafts of the furniture glides are fitted with screw fins to facilitate installation in the tubes (wall thickness 2 mm).

Product options on inquiry

- Shaft for tube diameter 20 mm is available with screw rib or clamp trips.
- Further shaft measures starting with 19x1-1,5
- Further base measures up to appr. 60 mm
- No materials possible for reinforcement or electrical diverting.

Order Number	α °	D mm	D1 mm	H mm	H1 mm	L mm	t mm
GGH2000 25/16x1,5-2	19 (-22)	25	16	9,5	15,5	24,5	1,5-2
GGH2000 25/16x2-2,5	19 (-22)	25	16	9,5	15,5	24,5	2-2,5
GGH2000 25/18x1,5-2	19 (-22)	25	18	9,5	15,5	24,5	1,5-2
GGH2000 25/18x2-2,25	19 (-22)	25	18	9,5	15,5	24,5	2-2,25
GGH2000 25/18x2,5-3	19 (-22)	25	18	9,5	15,5	24,5	2,5-3
GGH2000 25/19x1-1,5	19 (-22)	25	19	10,5	18	24,5	1-1,5
GGH2000 25/19x1,5-2	19 (-22)	25	19	10,5	18	24,5	1,5-2
GGH2000 25/20x1,5-2	19 (-22)	25	20	10,5	18	24,5	1,5-2
GGH2000 25/20x1,2-1,5 e.S.	19 (-22)	25	20	10,5	18	24,5	1,2-1,5
GGH2000 25/20x1,75-2 e.S.	19 (-22)	25	20	10,5	18	24,5	1,75-2
GGH2000 25/22x1,5-2	19 (-22)	25	22	10,5	18	24,5	1,5-2



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

Order Number	α °	D mm	D1 mm	H mm	H1 mm	L mm	t mm
GGH2000 25/25x1,5-2	19 (-22)	25	25	10,5	18	24,5	1,5-2
GGH2000 25/28x1,5-2	19 (-22)	25	28	10,5	18	24,5	1,5-2
GGH2000 30/16x1,5-2	19 (-22)	30	16	9,5	15,5	24,5	1,5-2
GGH2000 30/16x2-2,5	19 (-22)	30	16	9,5	15,5	24,5	2-2,5
GGH2000 30/18x1,5-2	19 (-22)	30	18	9,5	15,5	24,5	1,5-2
GGH2000 30/18x2-2,25	19 (-22)	30	18	9,5	15,5	24,5	2-2,25
GGH2000 30/18x2,5-3	19 (-22)	30	18	9,5	15,5	24,5	2,5-3
GGH2000 30/19x1-1,5	19 (-22)	30	19	10,5	18,5	24,5	1-1,5
GGH2000 30/19x1,5-2	19 (-22)	30	19	10,5	18,5	24,5	1,5-2
GGH2000 30/20x1,5-2	19 (-22)	30	20	10,5	18,5	24,5	1,5-2
GGH2000 30/20x1,2-1,5 e.S.	19 (-22)	30	20	10,5	18,5	24,5	1,2-1,5
GGH2000 30/20x1,75-2 e.S.	19 (-22)	30	20	10,5	18,5	24,5	1,75-2
GGH2000 30/22x1,5-2	19 (-22)	30	22	10,5	18,5	24,5	1,5-2
GGH2000 30/25x1,5-2	19 (-22)	30	25	10,5	18,5	24,5	1,5-2
GGH2000 30/28x1,5-2	19 (-22)	30	28	10,5	18,5	24,5	1,5-2