



### Product Group MFKJ

Machine feet made of stainless steel with two fixing holes (optional with antislip pad)



#### Material

- Base body: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The solid stainless steel design makes the foot highly resilient. The rounded shape makes cleaning easier.
- The machine foot can compensate for uneven floors up to 8°.
- The machine foot has two fixing holes
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The base is optionally available with a non-slip rubber plate that is firmly bonded to the stainless steel plate.
- Please order separately (MFJKxG, x = D)!

| D   | B  | H1 | H2 | d  | F max. | M   | WAF |    |
|-----|----|----|----|----|--------|-----|-----|----|
| mm  | mm | mm | mm | mm | kg     |     | mm  | mm |
| 90  | 32 | 17 | 5  | 13 | 6000   | M12 | 10  | x  |
| 90  | 32 | 17 | 5  | 13 | 6000   | M16 | 13  | x  |
| 90  | 32 | 17 | 5  | 13 | 6000   | M20 | 17  | x  |
| 90  | 32 | 17 | 5  | 13 | 6000   | M24 | 19  | x  |
| 90  |    |    |    |    |        |     |     |    |
| 110 | 44 | 17 | 5  | 13 | 6000   | M16 | 13  | x  |
| 110 | 44 | 17 | 5  | 13 | 6000   | M20 | 17  | x  |
| 110 | 44 | 17 | 5  | 13 | 6000   | M24 | 19  | x  |
| 110 | 44 | 17 | 5  | 13 | 6000   | M30 | 24  | x  |
| 110 | 44 | 17 | 5  | 13 | 6000   | M36 | 30  | x  |
| 110 |    |    |    |    |        |     |     |    |
| 150 | 62 | 17 | 5  | 16 | 6000   | M16 | 13  | x  |
| 150 | 62 | 17 | 5  | 16 | 6000   | M20 | 17  | x  |
| 150 | 62 | 17 | 5  | 16 | 6000   | M24 | 19  | x  |
| 150 | 62 | 17 | 5  | 16 | 6000   | M30 | 24  | x  |
| 150 | 62 | 17 | 5  | 16 | 6000   | M36 | 30  | x  |
| 150 |    |    |    |    |        |     |     |    |
| 180 | 74 | 17 | 5  | 16 | 6000   | M20 | 17  | x  |
| 180 | 74 | 17 | 5  | 16 | 6000   | M24 | 19  | x  |
| 180 | 74 | 17 | 5  | 16 | 6000   | M30 | 24  | x  |



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

| D   | B  | H1 | H2 | d  | F max. | M   | WAF | mm | 100 | 150 | 180 | 230 |
|-----|----|----|----|----|--------|-----|-----|----|-----|-----|-----|-----|
| mm  | mm | mm | mm | mm | kg     |     | mm  |    | mm  | mm  | mm  | mm  |
| 180 | 74 | 17 | 5  | 16 | 6000   | M36 | 30  |    | x   | x   | x   | x   |
| 180 | 74 | 17 | 5  | 16 | 6000   | M42 | 36  |    | x   | x   | x   | x   |
| 180 |    |    |    |    |        |     |     |    |     |     |     |     |

## Ordering example

• Group + D + M + Thread Length ---> MFKJ 110 M16 x 100