


Product Group JT/PP ISK

Adjustable feet with hexagonal adjusting screw and with hexagon in the thread end (swivelling base= B, fixed base= A)





Standard Colours

- black RAL 9005

Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Base: Polypropylene (PP)



Product information

- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

Product options on inquiry

- Further thread lengths/sizes
- Plastic base in special colours according to RAL-System

D	Type	F max.	H	H1	M	WAF	SW1	20	30	40	50	60	70	80	90	100
mm		kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
30	A	400	10	13,5	M8	13	4	x	x	x	x	x	x	x	x	x
30	B	400	10	15	M8	13	4	x	x	x	x	x	x	x	x	x
30	B	550	10	17	M10	17	5	x	x	x	x	x	x	x	x	x
58	B	550	19,5	27	M10	17	5	x	x	x	x	x	x	x	x	x

Ordering example

- Group + D + Type + M + Thread Length ---> JT/PP ISK 30 B M10x 60