


Product Group JT HE

Adjustable feet with stainless steel cover and hexagonal adjusting screw (swivelling base) for div. ground plates JTH BF/HP/GP




Standard Colours

- black RAL 9005

Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Cover: Stainless Steel
- Base: Polyamide (PA)



Product information

- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- *) = Production with assembly aid Pozidriv 2 in the base (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

Product options on inquiry

- Further thread lengths/sizes
- Hexagon socket in thread end (please look at JT HE ISK)

D	F max.	H	H1	M	WAF	16	20	30	40	50	60	70	80	90	100	120
mm	kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
38	400	13,5	20	M8	13	x	x	x	x	x	x	x	x	x	x	x
38	550	13,5	22	M10	17	x	x	x	x	x	x	x	x	x	x	x
38	650	13,5	24	M12	19			x	x	x	x	x	x	x	x	x
48	400	13,5	20	M8	13	x	x	x	x	x	x	x	x	x	x	x
48	550	13,5	22	M10	17	x	x	x	x	x	x	x	x	x	x	x
48	650	13,5	24	M12	19			x	x	x	x	x	x	x	x	x

Ordering example

- Group + D + M + Thread Length ---> JT HE 38 M10x 60