


Product Group 35

Articulated feet made of glass fibre reinforced polyamide (optional with self-sealing anti-slip plate 35G)




Standard Colours

- black

Material

- Base body: glass fibre reinforced polyamide (PA-GF)
- Anti-slip plate: elastic thermoplast (TPE)



Product information

- Polyamide base with spokes
- The ant-slip-plate is self-sealing.
- The machine foot can compensate for uneven floors up to 20°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

Product options on inquiry

- Further thread lengths/sizes

Order Number	D	F1 max.	F2 max.	H	H1	L	α	M	WAF
	mm	kg	kg	mm	mm	mm	°		mm
35 P - 50 / M16x70	50	100	500	20	40	70	20	M16	24
35 P - 50 / M20x70	50	100	500	20	40	70	20	M20	24
35 P - 50 / M20x120	50	100	500	20	40	120	20	M20	24
35 P - 60 / M16x70	60	100	500	20	40	70	20	M16	24
35 P - 60 / M20x70	60	100	500	20	40	70	20	M20	24
35 P - 60 / M20x120	60	100	500	20	40	120	20	M20	24
35 P - 80 / M16x70	80	100	500	20	40	70	20	M16	24
35 P - 80 / M20x70	80	100	500	20	40	70	20	M20	24
35 P - 80 / M20x120	80	100	500	20	40	120	20	M20	24
35 P - 100 / M16x70	100	100	500	20	40	70	20	M16	24
35 P - 100 / M20x70	100	100	500	20	40	70	20	M20	24
35 P - 100 / M20x120	100	100	500	20	40	120	20	M20	24
35G- 50	50								
35G- 60	60								
35G- 80	80								
35G- 100	100								